

INDASH by PANAVISE®

I-75130-509

Page 1 of 3

MOUNTING LOCATION:

Right Side of Climate Control

TOOLS REQUIRED:

Dash Tool, Hook tool
Phillips Head Screwdriver

PARTS INCLUDED:

(1)S7-2003 Mount

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

PART#: 75130-509

MFG: INFINITI

MODELS & YEARS:

Q60IPL Conv.14-15, G37 Conv.09-13 (Pg.1)
G25 2011-2012 (pg.1), G35 Sedan 07-08 (Pg.1)
Q40 14-16, G37 Coupe 08-13, G37 Sedan & Conv 09-13, Q40
2015 (Pg.1) QX50 14-17, EX 08-13, (P.2),
QX70 14-17, FX 09-13, (P.3)

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

STEP #1: G35 07-09 and G37 08-09 Start here: Push down on collar of shifter to release. With hook tool remove the clip that holds the shifter on by pushing on the triangle side to release the clip from the back.

G25 11-12, Q60 14-15, Q40 2015 and G37 10-13, Start here: With dash tool and your hands remove the small bezel piece from below the climate control releasing (2) metal clips and (4) plastic clips at the top of the bezel. Set aside. **Go to STEP#3**

STEP #2 Apply emergency brake. Shift transmission into N. With Hook/Dash tool remove the shifter bezel/ashtray bezel by starting at the back, lifting to release (1) clip on each side. Continue lifting to release shifter bezel from climate control bezel and set off to the side.

STEP #3: With Phillips head screwdriver remove (2) screws below the climate control. with your hands pull to release the climate control and set off to the left side.

STEP #4: Remove (1) Phillips screw in the upper right corner of the climate control/clock cavity. Place Indash by PanaVise Mount over screw hole and replace screw.

STEP #5: Replace the climate control and small bezel (10-13). Shifter bezel (08-10). **INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW INDASH by PANAVISE MOUNT.**



G35 Shifter Bezel Removal 07-09



Climate Control Removal Screws



Bezel below climate control 10-13



Bezel removed showing CC screws 10-13



InDash installed showing location ALL



05-15-18

There may be recent updates to this Instruction Sheet, please visit our website or contact PanaVise Products, Inc. for the latest revision as well as for the most complete up-to-date PanaVise *InDash Applications List*: 7540 Colbert Dr., Reno, NV, Phone: 800.759.7535, 775.850.2900, Fax: 800.395.8002, www.panavise.com. © 2018 PanaVise Products, Inc.

INDASH by PANAVISE®

I-75130-509

Page 2 of 3

MOUNTING LOCATION:

Right Side of Climate Control

TOOLS REQUIRED:

Dash Tool, Hook tool

Phillips Head Screwdriver

PARTS INCLUDED:

(1)S7-2003 Mount

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

PART#: 75130-509

MFG: INFINITI

MODELS & YEARS:

Q60IPL Conv.14-15, G37 Conv.09-13 (Pg.1)

G25 2011-2012 (pg.1), G35 Sedan 07-08 (Pg.1)

Q60 14-16, G37 Coupe 08-13, G37 Sedan & Conv 09-13, Q40

2015 (Pg.1) QX50 14-17, EX 08-13, (P.2),

QX70 14-17, FX 09-13, (P.3)

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

For EX / QX50 Start Here:

STEP #1: Safely Shift vehicle into (N) Neutral. With Dash tool - Hook Tool, Lift off the shifter bezel, starting from the back releasing (4) clips. tilt up bezel, pull back to release (3) plastic lugs from under climate control.

STEP #2 With Phillips screwdriver remove (2) screws under climate controls. Carefully tilt out on the bottom of the climate control/CD/clock panel, and pull down to release. there are (2) J-clips at the top sides that need to be released. NOTE: Careful to not damage the wires.

STEP #3: Remove the (1) Phillips screw to the upper right of the cavity below the display controls. Place the InDash by PanaVise Mount over the screw hole and replace the screw. Replace the bezels and screws in reverse order.

INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW INDASH by PANAVISE MOUNT.



Shifter Bezel Removal



ClimateControl removal screws



InDash installed showing location



Climate Control Removal Screws



05-15-18

INDASH by PANAVISE®

I-75130-509

Page 3 of 3

MOUNTING LOCATION:

Right Side of Climate Control

TOOLS REQUIRED:

Dash Tool, Hook tool

Phillips Head Screwdriver

PARTS INCLUDED:

(1)S7-2003 Mount

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

PART#: 75130-509

MFG: INFINITI

PART#: 75130-509

MODELS & YEARS:

Q60IPL Conv.14-15, G37 Conv.09-13 (Pg.1)

G25 2011-2012 (pg.1), G35 Sedan 07-08 (Pg.1)

Q60 14-16, G37 Coupe 08-13, G37 Sedan & Conv 09-13, Q40

2015 (Pg.1) QX50 14-17, EX 08-13, (P.2),

QX70 14-17, FX 09-13, (P.3)

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

For FX / QX70 Start Here:

STEP #1: Remove front top panel of the console box by prying from console box side with dash tool up and out to release (4) clips.

STEP #2 Remove console shifter top by lifting up to release a total of (6) clips. The top includes the cup holder and shifter indicator. Pull back enough to get at the bottom of the tray and power outlet assembly. Pull out at the bottom of the ashtray and power outlet assembly with hook tool to release all together (4) clips. Set it aside.

STEP #3: With Phillips head screwdriver remove (2) screws below the climate control. With your hands pull out and down to release (2) plastic clips & (3) lugs at top of climate control / CD/clock cover.

STEP #4: Remove upper right cavity screw, below display controls. Place InDash by PanaVise Mount over screw hole and replace screw.

STEP #5: Replace the climate control and shifter bezel in reverse order.

INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW INDASH by PANAVISE MOUNT.



Shifter Clip Removal



Shifter Bezel Removal



Climate Control Removal Screws



InDash installed showing location



05-15-18